

# Inflatable Tank

# Inflatable Tank

High-quality materials | Up to 56.000 Liters

Vallfirest inflatable tanks are a commitment to improving logistics in the creation of remote water points. They exponentially reduce assembly time and complexity compared to traditional tanks with a metallic structure and have more efficient features than floating collar tanks.




## 1 Configurations

Technical Specifications			
	12.000 L	25.000 L	56.000 L
Reference	DED5705-00003	DED5705-00002	DED5705-00001
Diameter	4 m   13 ft	4 m   13 ft	6 m   20 ft
Height	1 m   3.3 ft	2 m   6.5 ft	2 m   6.5 ft
Thickness	10 cm   4 in	10 cm   4 in	10 cm   4 in
Useful Height	85 cm   33.5 in	1,7 m   67 in	1,7 m   67 in
Capacity	12,000 L   3,170 gal	25,000 L   6,600 gal	56,000 L   14,800 gal
Material	PVC 2,600 g / m2	PVC 2,600 g / m2	PVC 2,600 g / m2
Bottom	Double layer, blue color	Double layer, blue color	Double layer, blue color
Connections	Two threaded 2" valves at the bottom	Two threaded 2" valves at the bottom	Two threaded 2" valves at the bottom
Color	Orange	Orange	Orange
Pump	1200W (2 units)	1200W (2 units)	1200W (2 units)
Inflation time	3 min.	3 min.	3 min.
Repair pack	PVC (2 units)	PVC (2 units)	PVC (2 units)
Transport bag	Included	Included	Included
Anchor points	8 metal rings around the perimeter	8 metal rings around the perimeter	8 metal rings around the perimeter
Weight	78 Kg   171 lbs	105,5 Kg   232 lbs	173,5 Kg   382 lbs
Folded dimensions	120 x 63 x 63 cm   47 x 25 x 25 in	160 x 70 x 70 cm   63 x 27 x 27 in	170 x 113 x 90 cm   67 x 44 x 35 in

## 2 Components included

### 2.1 Repair Kit

Includes patches for the base and structure and a plug for the inflation valve.



### 2.2 Anchoring Kit

Includes stakes, slings and a hammer.

#### DISCLAIMER

- These images are representative and may differ from the delivered kit

