



NEO
LEADER Fan
EASY POWAIR
TECHNOLOGY

PETROL-DRIVEN FAN

MT240

A very concentrated and ultra-powerful jet of air due to an optimal combination of:

- A high-strength propeller matched to the power of the engine
- A red double-layer monobloc shroud made of reinforced high-density polyethylene
- A high-tech composite grille

Positioning from 0.90 m to 6 m in front of a door without loss of power for:

- More space to move about
- Less noise inside the building

Automatic optimal +10° tilt

- Automatic optimal +10° tilt

Precise tilt adjustment from +10° to +20°

- For optimization of direction of air stream up entrance steps

Protective frame

- With grey epoxy coating

Stable & easy to handle

- With large rear wheels

Compact

- For easy storage in vehicle trunks

Integrated stabilizer prop at rear

- Also enables fan to be tilted to -10° for downward ventilation

MULTI-APPLICATION

- Indoor and outdoor: Protected against splashing water
- Alone, at the entrance of a building in VPP
- In VPP combined with other fans
- Blowing with ducts (optional)
- As a foam generator with its high expansion adapter (optional)
- As a misting device (option)

CHARACTERISTICS

	MT240 NEO
Reference	I60.10.060N
Open air flow	68 300 m ³ /h
PPV air flow according to AMCA	36 280 m ³ /h
Weight	40,5 kg
Dimensions L x H x D	550 x 560 x 515 mm
Propeller diameter	420 mm
Run time at full speed	2h00
Engine	Engine HONDA GX 200 (4-stroke) Automatic engine cutout if oil runs out. Assembly inspected and approved by Honda Motor Co., Ltd
Engine power	5.5 HP according to standard SAE J1349 of 2007
Noise level	93 dB at 3 m
Ventilation type	PPV blowing
Application	Single door, e.g. house, small apartment block
Garantees	5 years / 3 years

OPTIONS – ACCESSORIES

CO-reducing LEADER Cat catalytic converter	Ref. I60.20.142
Mister without coupling	Ref. I60.20.104
High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct	Ref. I60.20.105
Hour meter	Ref. I60.20.135
Exhaust adapter	Ref. I60.20.145
Exhaust extension (length: 2.5m)	Ref. I60.20.012
Protective cover	Ref. I60.20.017
5m ventilation duct	Ref. I60.20.152

REDUCED COST OF OWNERSHIP

Very low maintenance due to the very robust design and materials used.

ZF.03.432.EN.1