



LEADER Fan
EASY POWAIR
TECHNOLOGY

**PETROL-DRIVEN
FAN**

MT280

A concentrated, powerful jet of air due to:

- High-strength propeller matched to the power of the motor
- Double-layer aluminum/ABS thermoplastic red shroud
- Metal grille

Positioning from 0.90 m to 6 m in front of a door without loss of power for:

- More space to move about
- Less noise inside the building

Automatic optimal +10° tilt

- When handle raised

Precise tilt adjustment

- From +10° to +20° for optimization of direction of air stream up entrance steps

Protective frame

- With grey epoxy coating

Stable & easy to handle

- With large rear wheels

MULTI-APPLICATION

- Indoor and outdoor: Protected against splashing water
- Alone, at the entrance of a building in VPP
- In VPP combined with other fans
- Blowing with ducts (optional)
- As a foam generator with its high expansion adapter (optional)
- As a misting device (option)

CHARACTERISTICS

	MT280
Reference	I60.10.048
Open air flow	117 100 m3/h
PPV air flow according to AMCA	-
Weight	69 kg
Dimensions L x H x D	710 x 780 x 617 mm
Propeller diameter	570 mm
Run time at full speed	1h20
Engine	HONDA GX 390 (4-stroke) Automatic engine cutout if oil runs out. Assembly inspected and approved by Honda Motor Co., Ltd
Engine power	11.7 HP according to standard SAE J1349 of 2007
Noise level	99 dB at 3 m
Ventilation type	PPV blowing
Application	Single door (e.g. house, small apartment block) and double door (e.g. tall apartment block, mid-size industrial unit)
Garantees	5 years / 3 years

OPTIONS - ACCESSORIES

Mister without coupling	Ref. I60.20.104
High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct	Ref. I60.20.116
Hour meter	Ref. I60.20.135
5m ventilation duct	Ref. I60.20.153
Exhaust adapter	Ref. I60.20.125
Exhaust extension (length: 2.5m)	Ref. I60.20.012
Protective cover	Ref. I60.20.097
-10° prop for negative tilt of fan	Ref. I60.20.108

REDUCED COST OF OWNERSHIP

Very low maintenance due to the very robust design and materials used.

ZF.03.427.EN.1