



LEADER Fan
EASY POW'AIR
TECHNOLOGY

**PETROL-DRIVEN
FAN**

MT296

A concentrated, powerful jet of air due to:

- High-strength propeller matched to the power of the motor
- Double-layer aluminum/ABS thermoplastic red shroud
- Metal grille

Positioning from 0.90 m to 6 m in front of a door without loss of power for:

- More space to move about
- Less noise inside the building

Automatic optimal +10° tilt

- When handle raised

Precise tilt adjustment

- From +10° to +20° for optimization of direction of air stream up entrance steps

Protective frame

- With grey epoxy coating

Stable & easy to handle

- With large rear wheels

MULTI-APPLICATION

- Indoor and outdoor: Protected against splashing water
- Alone, at the entrance of a building in VPP
- In VPP combined with other fans
- Blowing with ducts (optional)
- As a foam generator with its high expansion adapter (optional)
- As a misting device (option)

CHARACTERISTICS

MT296	
Reference	I60.10.045
Open air flow	128 950 m ³ /h
PPV air flow according to AMCA	-
Weight	76,7 kg
Dimensions L x H x D	710 x 780 x 678 mm
Propeller diameter	570 mm
Run time at full speed	1h50
Engine	B&S Vanguard two-cylinder engine (4-stroke)
Engine power	16 HP according to standard SAE J1349 of 2007
Noise level	98.3 dB at 3 m
Ventilation type	PPV blowing
Application	Single door (e.g. house, small apartment block) and double door (e.g. high rise buildings, mid-size industrial unit)
Garantees	5 years / 3 years

OPTIONS - ACCESSORIES

Mister without coupling	Ref. I60.20.111
High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct	Ref. I60.20.116
Hour meter	Ref. I60.20.135
5m ventilation duct	Ref. I60.20.153
Exhaust extension (length: 2.5m)	Ref. I60.20.012
Protective cover	Ref. I60.20.097
-10° prop for negative tilt of fan	Ref. I60.20.108

REDUCED COST OF OWNERSHIP

Very low maintenance due to the very robust design and materials used.

ZF.03.432.EN.1