

3AA

INTRINSICALLY SAFE INTRANT™ DUAL-LIGHT ANGLE LIGHT

XPP-5566RX/GX

NIGHTSTICK
Life Depends on Light™



HEAD ROTATES 90°

EXCLUSIVE 45°
DOWNWARD FLOODLIGHT

DUAL
LIGHT
TECHNOLOGY



Head rotates 90° – directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches independently control separate LEDs



Heavy-duty, clip and V-ring securely holds tight to gear in any situation



AVAILABLE IN HI-VIZ GREEN.

205 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

INTRANT®**DUAL-LIGHT™ ANGLE LIGHT****3AA****ITEM NUMBER/UPC**

XPP-5566RX (Red), 0 17398 80629 9
 XPP-5566GX (Green), 0 17398 80628 2

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, UKCA, InMetro, NFPA

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 200L, 11 hrs. runtime
- MEDIUM: 110L, 18 hrs. runtime
- LOW: 60L, 33 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 11 hrs. runtime
- MEDIUM: 40L, 18 hrs. runtime
- SURVIVAL: 20L, 33 hrs. runtime

DUAL-LIGHT

- 205L, 11 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 11.1 oz (315g)(with batteries)

BATTERY







- 3AA batteries (included)

WARRANTY



- Limited Lifetime Warranty

WHAT'S INCLUDED

- Angle light
- AA battery carrier
- 3AA batteries
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	11h	33h	11h
	401m		
	40256cd		
			
			

Segurança

oCP 0034 **INMETRO**
 Ex is op is I Ma
 Ex is op is IC T4 Ga
 (20°C ≤ Tamb ≤ +40°C)
 NCC 18.0110 X

UL LISTED
 E 487795
 ID 4003544
 ELECTRICAL SAFETY
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

Bayco Product Inc. XPP-5566
 640 S. Sanden Blvd., Wylie, TX 75098

Ex is FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS LANTERNA Ex is PARA USO EM LOCOS PERIGOSOS
 Para uso com a bateria de 3 AA ou com o carregador de 3 AA Energy Type EN91 or E91 batteries only
 Para uso com a bateria de 3 AA ou com o carregador de 3 AA Energy Type EN91 ou E91

CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G T110°C © I M1 Ex is op is I Ma Ex is op is I Ma
 CLASS I ZONE 0 AEx ia IIC T4 Ga © I 1 G Ex is op is IIC T4 Ga Ex is op is IIC T4 Ga
 US Patents 9,713,217 & 10,119,663

DEMKO 17 ATEX 1927 UL22XEX2426 IECEx I.E. 17.0082 Control Drawing: 5566-CERT-DWG1-03
 22-ANAB0-020X -20°C ≤ Tamb ≤ +40°C For Battery Charger Connection see Instruction Manual Drawing: 5562-68-MECH-DWG1-09

Meets the requirements of NFPA-1971-8.6 (2013) IP-67 3.7V/Cell Lithium IP-67 SEE INSTRUCTION MANUAL MFG MM-YY
 Um: 10V VOIR MANUEL

CERTIFIED