

# Xtreme Mask

Certified - Model: VFT XTREME PROTECTIVE MASK AVA1317-AAA0A

Maximum protection against all types of particles and vapors.



# Xtreme Mask

Maximum protection against all types of particles and vapors\*.

The **Xtreme Mask** is a multi-purpose device designed for complete face and respiratory tract protection in extreme conditions.

\*Read the instructions and verify the limitations of use.

## What does the Xtreme Mask include?

- Protective mask with a half-mask.
- 2 P3 R particle filters

## Suggestion for use

### Firefighting (included)

P3 R filter directly connected to the half-mask.

Heat, humidity, radiation, incandescent particles, microparticles, nanoparticles, smoke, fog, aqueous dispersion, viruses, bacteria, enzymes, proteins.

### Finish and interface (optional)

ABEK1P3 R filter directly connected to the half-mask. All of the above plus gases and organic and inorganic vapors, acids, amine and formaldehyde in slow combustion.



## Standards

### Textile

<b>EN ISO 11612:2015</b>	Protective clothing. Protective clothing against heat and flame. Minimum performance requirements.
<b>EN ISO 13688:2013</b>	Protective clothing. General requirements.
<b>EN 15614:2007</b> (The PPE also complies with points 5, 6, 7, 8 and 9.1 of standard EN 15614. For protection compliant with EN 15614, it must be used along with a complete suit compliant with this standard).	Protective clothing for firefighters. Laboratory testing methods and requirements for forestry clothing.

### Half-mask

<b>EN 140:19998</b>	Respiratory protection equipment. Half-mask.
---------------------	--

### P3 R filter

<b>EN 143:2004 + A1:2006</b>	Respiratory protection equipment. Filters against particles. Requirements, testing, marking.
------------------------------	--

## Technical specifications

### Textile

<b>Fabric composition</b>	65% Lenzing® F.R.   30% Nomex®   5% Kevlar®
<b>Fabric grammage</b>	270 g/m²
<b>Fabric composition in respiration area</b>	64% Viscose   34% Aramide   2% Anti-static
<b>Thread composition</b>	100% meta-aramid thread.
<b>Composition of silver reflective fabric</b>	100% F.R. cotton.
<b>Operating temperature range</b>	From -35°C to 60°C.

### Half-mask

<b>Material</b>	Hypoallergenic thermoplastic elastomer.
<b>Protection</b>	Against all types of particles, solids and liquids, viruses, bacteria.
<b>Connection type</b>	Bayonet.

### P3 R filter

<b>Protection</b>	Against all types of particles, solids and liquids, viruses, bacteria.
<b>Connection type</b>	Direct mask bayonet.
<b>Total weight</b>	329 g.

## Optional filters\*



### ABEK1P3 COMBINED FILTER

ABEK1P3 reusable combined filter for particles, dust, smoke, fog, viruses, bacteria and gases and organic and inorganic vapors, acids, amine and formaldehyde in slow combustion.

<b>Protection</b>	Against solid particles, liquids, bacteria and viruses.
<b>Standard</b>	EN 14387:2004+A1:2008
<b>Connection type</b>	Direct mask bayonet.
<b>Weight</b>	Filter: 151 g.   Filter + half-mask + textile mask: 412 g.

Any questions? Contact us: [clientes@vallfirest.com](mailto:clientes@vallfirest.com) | T. +34 938 678 779